

Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

4

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A method for printing wallpaper onto a web of media, comprising the steps of:
  - utilizing an on-demand printer comprising a cabinet, in which is located a media path which extends from a media loading area to a winding area, ~~there being a~~ printhead located in the media path, and a processor which accepts operator inputs from one or more input devices;
  - using one or more input devices which communicate with the processor to capture data from an operator regarding a specification for an operator's requirements including a selection of a pattern, said selection being communicated by input of a symbol of the selected pattern;
  - using the processor to operatively control the printer according to the data; and
  - printing a single roll of wallpaper, on demand, according to a selected pattern.
2. (Original) The method of claim 1, further comprising the step of:
  - representing the pattern as a symbol which can be captured as the data by an input device which communicates with the processor.
3. (Original) The method of claim 1, further comprising the step of:
  - storing to a storage device accessible to the processor and internal to the cabinet, a plurality of selectable files for describing patterns for printing onto the media.
4. (Original) The method of claim 1, further comprising the step of:
  - providing the printer with a video display for depicting the selected pattern.
5. (Original) The method of claim 4, further comprising the step of:
  - using the video display as a touch screen input device to capture operator preferences.
6. (Original) The method of claim 1, further comprising the step of:

Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

5

providing the printer with a scanner for capturing data that specifies a selected pattern.

7. (Currently Amended) The method of claim 4, further comprising the step of:  
using the video display to display information that relates to the configuration of the printer.
8. (Currently Amended) The method of claim 1, wherein:  
printing a roll of wallpaper according to a selected pattern and the configuration of the printer further comprises inserting a blank core into a winding area, in or on the printer and accessible to an operator;  
winding the web onto the core after the web has been printed on; and  
severing the wound core from the web.
9. (Original) The method of claim 8, wherein:  
winding the web is performed by winding a length of a printed web onto the core;  
the length being determined in advance;  
the length being part of the configuration of the printer.
10. (Withdrawn) The method of claim 8, wherein:  
the core is contained in a tote during the winding.
11. (Withdrawn) The method of claim 9, wherein:  
winding the web is further performed by slitting the web, within the printer, to one or more specified widths prior to winding;  
the one or more specified widths being a part of the printer configuration, having been communicated through one of the input devices.
12. (Currently Amended) The method of claim 1, further comprising the step of:  
providing one or more collections of patterns;  
each pattern in a collection having a said symbol which can be used as an operator input.
13. (Currently Amended) The method of claim 1, wherein:

Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

6

the specification for an operator's requirements comprises a pattern and ~~the a~~  
configuration of the printer;

the configuration being one or more parameters selected from the group comprising:  
roll length, a roll slitting arrangement, one or more modifications to the pattern, or a  
selection of media to be printed on.

14. (Original) The method of claim 1, wherein utilizing an on-demand printer further  
comprises:

loading a media cartridge into the printer, the cartridge containing a unprinted web of  
media; and

using a motor in the printer to advance the unprinted web into the path;  
automatically threading the media from the loading area, to the winding area.

15. (Original) The method of claim 1, wherein utilizing an on-demand printer further  
comprises:

loading a media tote into the winding area;  
winding a printed roll of wallpaper onto a core inside the tote; and  
severing the printed roll on the core from the web.

16. (Original) The method of claim 1, wherein utilizing an on-demand printer further  
comprises:

loading an empty core into the winding area;  
winding a printed roll of wallpaper onto a core; and  
severing the printed roll on the core from the web using an automated cutting  
mechanism inside the printer, the cutting mechanism receiving a signal for commencing  
cutting from the processor.

17. (Withdrawn) The method of claim 1, wherein printing a roll of wallpaper according  
to a selected pattern further comprises:

using a full width, stationary color printhead to print onto the web while it is in  
motion along the path.

18. (Withdrawn) The method of claim 17, further comprising the step of:  
drying the web after it is printed on but before it is dispensed by the printer.

Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

7

19. (Withdrawn) The method of claim 18, wherein drying further comprises:  
admitting the printed web into a compartment in an internal dryer and exposing the web to a stream of heated air.
20. (Withdrawn) The method of claim 17, further comprising the step of:  
heating the web with a pre-heater platen located under the path before the web passes the printhead.
21. (Withdrawn) A method as claimed in claim 1 wherein the web of blank media is printed by the printhead at a rate exceeding 0.02 square meters per second (775 square feet per hour).
22. (Withdrawn) A method as claimed in claim 1 wherein the web of blank media is printed by the printhead at a rate exceeding 0.1 square meters per second (3875 square feet per hour).
23. (Withdrawn) A method as claimed in claim 1 wherein the web of blank media is printed by the printhead at a rate exceeding 0.2 square meters per second (7750 square feet per hour).
24. (Withdrawn) A method as claimed in claim 1 wherein the printhead has more than 7680 nozzles.
25. (Withdrawn) A method as claimed in claim 1 wherein the printhead has more than 20,000 nozzles.
26. (Withdrawn) A method as claimed in claim 1 wherein the printhead has more than 100,000 nozzles.
27. (Withdrawn) A method as claimed in claim 1 wherein the printhead has more than 250,000 nozzles.

Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

8

28. (Withdrawn) A method as claimed in claim 1 wherein the printhead prints ink drops with a volume of less than 5 picoliters.

29 (Withdrawn) A method as claimed in claim 1 wherein the printhead prints ink drops with a volume of less than 3 picoliters.

30. (Withdrawn) A method as claimed in claim 1 wherein the printhead prints ink drops with a volume of less than 1.5 picoliters.

31. (Currently Amended) A method as claimed in claim 1 wherein:  
the printer is a self contained printer for producing rolls of wallpaper;~~the printer comprising:~~  
~~a cabinet in which is located a media path which extends from a media cartridge loading area to a winding area;~~  
~~the printhead is a full width digital color printhead located in the media path;~~  
~~a processor which accepts the operator inputs which are accepted by the processor -are~~  
used to configure the printer for producing a particular roll; and  
the winding area is adapted to removably retain a core and wind onto it, wallpaper produced by the printer.

32. (Original) A method as claimed in claim 1 wherein utilizing an on-demand printer further comprises:  
loading a media cartridge into the printer, the media cartridge, comprising:  
a case in which a roll of blank media may be deployed;  
the case having two halves, hinged together, an area between the two halves, when closed, defining a media supply slot; and  
the case having internally and adjacent to the slot, a pair of rollers, at least one of the rollers being a driven roller which is supported at each end, by the case, for rotation by an external motor.

33. (Withdrawn) A method as claimed in claim 1 further comprising the step of providing a consumer tote for carrying the roll of wallpaper, the tote comprising:  
a disposable exterior in which is formed a main access flap and a pair of core access openings; and

Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

9

the tote having an interior in which is located a disposable core which is aligned with the access openings.

34. (Withdrawn) A method as claimed in claim 1 wherein the printer has a transverse cutter, the transverse cutter comprising:

- a chassis having end plates;
- the end plates being separated to allow a web of media to pass between them;
- the end plates supporting between them a cutting blade; and
- the blade supported at each end to perform a cutting motion which begins on one side of the web and finishes on an opposite side of the web.

35. (Withdrawn) A method as claimed in claim 1 wherein the printer has a slitting mechanism, the slitting mechanism comprising:

- a chassis having end plates;
- the end plates being separated by a transverse portion of the chassis to allow a web of media to pass between them;
- one or more rotating slitting shafts extending between the end plates, each shaft having one or more slitters arranged along its length, each slit having a cutting edge; and
- the slitting mechanism selectively engageable to either enter or not enter a path followed by the web according to an input provided by an operator of the printer.

36. (Withdrawn) A method as claimed in claim 1 wherein the printer has a dryer, the dryer comprising:

- a compartment with a top opening for receiving a media web fed from the printer;
- a source of heated air located above the top opening for blowing heated air into the opening to dry printing on the media web.

37. (Currently Amended) A method as claimed in claim 1 wherein the printer comprises:

- ~~a cabinet in which is located a media path which extends from a media loading area to a winding area;~~
- ~~a printhead located in the media path;~~
- ~~a processor which accepts the operator inputs from one or more input devices~~  
~~which accepted by the processor~~ are used to configure the printer for producing a particular roll; and

Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

10

the winding area is adapted to removably retain a core and wind onto it, wallpaper produced by the printer wherein,

the length and design of the roll are determined by the operator inputs.

38. (Currently Amended) A method as claimed in claim 1 further comprising the steps of:

~~utilizing an on-demand printer comprising a cabinet in which is located a media path which extends from a media loading area to a printhead and from the printhead to a dispensing slot;~~

using the one or more printer input devices ~~which to~~ communicate with ~~a the~~ processor so as to capture data regarding one or more customer's requirements;

the data comprising at least a customer selected pattern;

printing a roll of wallpaper, onto a web of blank media, on demand, according to the selected pattern; and

charging a customer for the roll.

39. (Cancelled).

40. (Original) A method as claimed in claim 1 wherein the printer comprises:

a frame in which is located a media path which extends from a media loading area to a winding area;

a printhead located across the media path;

one or more input devices for capturing operator instructions;

a processor which accepts operator inputs which are used to configure the printer for producing a particular roll; and

the winding area adapted to removably retain a core and wind onto it, wallpaper produced by the printer.

41. (Withdrawn) A method as claimed in claim 1 for printing wallpaper onto a web of media further comprising the steps of:

utilizing an on-demand printer comprising a cabinet in which is located a media path, there being a full width printhead located across the media path, there being a processor which accepts operator inputs from one or more input devices and which controls the printer;

Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

11

using one or more input devices which communicate with the processor to capture data from an operator regarding a specification;  
running the printer according to the data;  
printing a single roll of wallpaper, on demand, according to a selected pattern and configuration;  
changing the pattern according to a new datum from an operator; and  
then printing a new roll onto the same web.

42. (Withdrawn) A method as claimed in claim 1 for drying the moving web of media in the printer, the method further comprising the steps of:

loading the web in a path that traverses a compartment in a dryer within the printer, the compartment having an opening across the top;  
allowing the moving web to descend into the compartment, as required; and  
blowing heated air from above the opening.

43. (Withdrawn) A method as claimed in claim 1 for supplying the media web to the wallpaper printer, the method further comprising the steps of:

opening a reusable case;  
placing into the case a core onto which has been located a supply roll of blank wallpaper media;  
supporting the core for rotation within the case;  
leading a free edge of the roll between a pair of rollers and past an edge of the open case; then  
with the rollers located within the case and on either side of the web, closing the case and loading it into a printer.

44. (Withdrawn) A method as claimed in claim 1 wherein the printer has a printhead assembly which prints onto a moving web that follows a path, the assembly comprising:

a full width printhead located across the path;  
the printhead comprising a color printhead which is at least as wide as the web;  
the printhead being supplied with a number of different inks which are remote from the printhead and which supply the printhead through tubes.

45. (Withdrawn) A method as claimed in claim 1 wherein the printer further comprises:



Appln No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

12

a housing in which is located a media path which extends from a blank media intake to a wallpaper exit slot;

a multi-color roll width removable printhead located in the housing and across the media path;

the printhead being supplied by separate ink reservoirs, the reservoirs connected to the printhead by an ink supply harness, there being a disconnect coupling between the reservoirs and the printhead;

one or more input devices for capturing operator instructions;

a processor which accepts operator inputs which are used to configure the printer for producing a particular roll.

46. (Withdrawn) A method as claimed in claim 1 further comprising the step of providing a consumer tote for carrying the roll of wallpaper, the tote comprising:

a disposable exterior in which is formed a main access flap and a pair of core access openings;

the tote having an interior in which is located a disposable core which is aligned with the access openings;

both openings exposing a moulded coupling, one coupling attached to each end of the core, at least one of the couplings being a driven coupling and adapted to engage a driving spindle that rotates the core.

47. (Withdrawn) A method as claimed in claim 1 wherein the printer has a removable printhead assembly which prints onto a moving web, comprising:

a full width stationary printhead located on a rail along which it slides for service and removal;

a number of replaceable ink reservoirs which supply the printhead with different inks;

the printhead comprising a color printhead which is at least as wide as the web; and

the printhead being supplied with the different inks through tubes which can be disconnected so the printhead may be removed.

48. (Currently Amended) A method as claimed in claim 1 wherein:

the printer is a self threading printer for producing rolls of wallpaper, comprising:

App'n No. 10/760,256  
Amdt. Dated August 31, 2005  
Response to Office Action of June 23, 2005

13

a the media loading area is adapted to support a media cartridge in a position so that a media supply slot of the cartridge is closely adjacent to a pilot guide;

~~a cabinet housing a~~ the media path ~~which extends from the pilot guide to a printed media dispensing slot;~~

a the printhead is located across the media path;

~~a processor which accepts the operator inputs which accepted by the processor~~ are used to configure the printer for producing a particular roll;

a motor is located within the cabinet for advancing a media web out of the media cartridge; and

one or more other motors ~~adapted~~ are provided to urge the media along the path and out of the slot.

49. (Cancelled).